

# CLASSIC-V-SERIES-3U

## Classic V

3U

- Engineered to provide secure transport for rack mountable electronics
- Available in 3U, 4U, 5U, 7U, and 9U
- $\bullet$  Equipment payload weight ranges for 3U 5U = 80-100 lbs. (36-45 kg) per case
- Equipment payload weight ranges for 7U 9U = 100-170 lbs. (45-77 kg) per case
- Black case with Anti-Reflective zinc cobalt black (HCB) catch-and-strike hardware
- 2 Lockable Cable Catches per lid to provide security for your equipment
- Black stainless steel handles
- Molded stacking ribs and coupling catches to secure cases when stacked
- Lid hangers for lid storage while in use
- $\bullet$  19" (48 cm) wide, 33" (83 cm) deep fixed square hole frame for universal equipment fit
- Choice of SAE 10-32 or Metric M6 clip nuts
- Sealed gasket and PRV keeps container watertight and eliminates over pressurization
- 4 removable 3.5" (8.9 cm) heavy duty bottom casters
- REACH and RoHs compliant



#### **DIMENSIONS**

**Exterior (L×W×D)** 45.80 x 27.00" x 12.30 (116.3 x 68.6 x 31.2 cm)

 Rack Height
 5.25" (13.3 cm)

 Rack Depth
 33.00" (83.8 cm)

 Interior Lid Depth
 2.50" (6.4 cm)

 Interior Back Lid Depth
 5.25" (13.3 cm)

#### **MATERIALS**

**Body** RotoMolded Polyethylene

O-Ring Silicone Sponge
Purge Body Aluminum

Hardware Stainless Steel (Black Oxide) / RoHs Nickel Black

Frame Steel (Clear Coated)

### **COLOURS**

Black

#### WEIGHT

**Weight** 51.00 lbs (23.1 kg)