



## CLASSIC-V-SERIES-4U

### Classic V

4U

- Engineered to provide secure transport for rack mountable electronics
- Available in 3U, 4U, 5U, 7U, and 9U
- Equipment payload weight ranges for 3U - 5U = 80-100 lbs. (36-45 kg) per case
- Equipment payload weight ranges for 7U - 9U = 100-170 lbs. (45-77 kg) per case
- Black case with Anti-Reflective zinc cobalt black (HCB) catch-and-strike hardware
- 2 Lockable Cable Catches per lid to provide security for your equipment
- Black stainless steel handles
- Molded stacking ribs and coupling catches to secure cases when stacked
- Lid hangers for lid storage while in use
- 19" (48 cm) wide, 33" (83 cm) deep fixed square hole frame for universal equipment fit
- Choice of SAE 10-32 or Metric M6 clip nuts
- Sealed gasket and PRV keeps container watertight and eliminates over pressurization
- 4 removable 3.5" (8.9 cm) heavy duty bottom casters
- REACH and RoHS compliant



### DIMENSIONS

|                                |   |
|--------------------------------|---|
| <b>Exterior (LxWxD)</b>        | 45.80 x 27.00" x 14.60 (116.3 x 68.6 x 37.1 cm) |
| <b>Rack Height</b>             | 7.00" (17.8 cm)                                 |
| <b>Rack Depth</b>              | 33.00" (83.8 cm)                                |
| <b>Interior Lid Depth</b>      | 2.50" (6.4 cm)                                  |
| <b>Interior Back Lid Depth</b> | 5.25" (13.3 cm)                                 |

### MATERIALS

|                   |   |
|-------------------|---|
| <b>Body</b>       | RotoMolded Polyethylene                           |
| <b>O-Ring</b>     | Silicone Sponge                                   |
| <b>Purge Body</b> | Aluminum  |
| <b>Hardware</b>   | Stainless Steel (Black Oxide) / RoHS Nickel Black |
| <b>Frame</b>      | Steel (Clear Coated)                              |

### COLOURS

■ Black

### WEIGHT

|               |                     |
|---------------|---------------------|
| <b>Weight</b> | 54.00 lbs (24.5 kg) |
|---------------|---------------------|