

1460 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Also available with EMS Organizer and Dividers
- Top lid opens up to 180° for on-the-field anti-roll stability when
- open

Watertight, crushproof, and dustproof

Automatic Pressure Equalization Valve - balances interior pressure, keeps water out

- Comfortable rubber over-molded handles
- Easy open Double Throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



1460 Standard



1460AALG With Custom Foam for 9430 / 9435



1460NF No Foam



1460WF With Foam

DIMENSIONS

| Interior (L×W×D) | 18.54 x 9.92" x 10.92 (47.1 x 25.2 x 27.7 cm) |
|-----------------------|---|
| Exterior (L×W×D) | 20.85 x 12.73" x 12.75 (53 x 32.3 x 32.4 cm) |
| Lid Depth | 4.91" (12.5 cm) |
| Bottom Depth | 6.01" (15.3 cm) |
| Total Depth | 10.92" (27.7 cm) |
| Int Volume | 1.16 ft ³ (0.033 m ³) |
| Padlock Hole Diameter | 5/16" (12.7 cm) |

MATERIALS

| Body | Polypropylene |
|--------|-----------------|
| Latch | EXL |
| O-Ring | Polymer |
| Pins | Stainless Steel |

| Foam | Polyurethane | |
|------------|--------------------------------|--|
| Purge Body | ABS | |
| Purge Vent | 3 Micron Hydrophobic Non-Woven | |

COLOURS

Black

WEIGHT

| Weight With Foam | 12.48 lbs (5.7 kg) |
|------------------|---------------------|
| Weight Empty | 8.75 lbs (4 kg) |
| Buoyancy | 82.00 lbs (37.2 kg) |

TEMPERATURE

| Minimum Temperature | -40°F (-40 °C) |
|---------------------|-----------------|
| Maximum Temperature | 210°F (98.9 °C) |

yes

CERTIFICATIONS


IP67

OTHER

Military

ACCESSORIES





1507 Quick Mounts - set of 4

1506TSA TSA Lock



1500D Desiccant Silica Gel