

# 1510

## Protector

Carry-On Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Maximum airline carry on size\*
- · Strong polyurethane wheels with stainless steel bearings
- Watertight, crushproof, and dustproof
- Automatic Pressure Equalization Valve balances interior pressure, keeps water out
- Comfortable rubber over-molded top and side handles
- Easy open Double Throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension handle
- Stainless steel hardware and padlock protectors
- Peli's legendary lifetime guarantee\*\*
- \* Check with your airline for exact measurement requirements.
- \* Where applicable by law



# **CONFIGURATIONS**



1510 Standard



1514 With Padded Dividers



1510NF No Foam



**1510TP** With TrekPak Divider System



1510WF With Foam



**1510TPF** TrekPak / Foam Hybrid

#### **DIMENSIONS**

Interior (L×W×D) 19.75 x 11.00" x 7.60 (50.2 x 27.9 x 19.3 cm) Exterior (L×W×D) 22.00 x 13.81" x 9.00 (55.9 x 35.1 x 22.9 cm)

 Lid Depth
 1.79" (4.5 cm)

 Bottom Depth
 5.79" (14.7 cm)

 Total Depth
 7.58" (19.3 cm)

 Int Volume
 0.96 ft³ (0.027 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

#### **MATERIALS**

**Body** Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

#### **COLOURS**

Black

Desert Tan

32.43 lbs (14.7 kg)

Yellow

## WEIGHT

 Weight With Foam
 13.60 lbs (6.2 kg)

 Weight Empty
 11.99 lbs (5.4 kg)

 Buoyancy
 64.15 lbs (29.1 kg)

 Weight With TrekPak / Foam Hybrid
 14.94 lbs (6.8 kg)

## **TEMPERATURE**

**Master Pack Weight** 

**Minimum Temperature** -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

## **CERTIFICATIONS**

IP67 Def Stan 81-41 STANAG 4280

## **OTHER**

Wheels 2
Extendable Handle yes
Master Pack 2
Nameplate yes
Reduced Area yes
Military yes

# **ACCESSORIES**



**1511** 4 pc. Replacement Foam Set



**1513** Replacement O-ring



**1515** Padded Divider Set



**1519** Lid Organizer



**1510EUTP** TrekPak Case Divider Kit



**1507** Quick Mounts - set of 4



**1506TSA** TSA Lock



**1500D** Desiccant Silica Gel



**1510MP** EZ-Click™ MOLLE Panel