1726
Air

Peli™ Air cases are the toughest and lightest cases Peli has to offer. Designed with a super-light proprietary HPXA™ polymer construction, each Peli Air case is up to 40 percent lighter than an average polymer case yet still extremely durable. Peli Air cases are waterproof, crushproof, and dustproof.
The Peli 1726 Air Case provides protection for multiple weapons systems, survey equipment, and professional gear transport. Designed to pack efficiently into standard Conex containers for streamlined logistics, the 1726 Air delivers weight saving construction, while maintaining the same trusted dimensions. Available with pick and pluck foam or case only, the Peli 1726 Air Case will lighten the load while protecting your mission-critical equipment.



• Premium HPX[A] Construction: Up to 40% lighter than equivalent cases, delivering uncompromising strength and impact resistance without the fatigue.
• Certified Toughness: IP67-Rated and rigorously tested to MIL-STD specifications to guarantee unrivaled protection in extreme conditions.
• Secure 2” Press & Pull™ Latches: Engineered for secure closure and effortless, fast access under pressure.
• Dual Automatic Pressure Equalization Valves: Rapidly balances interior pressure while keeping water and dust out of your protective solution.
• Interlocking Design: Molded top ribs and bottom stand-offs provide rock-solid stacking and stability during transport.
• Heavy-Duty Mobility: Equipped with rugged, smooth-rolling wheels and heavy-duty rubber overmolded handles for confident transport of heavy payloads.
• EZ-Click™ MOLLE Panel Compatible: Ready to integrate with the 1500MP panel for customized, secure lid organization.
• Integrated Card Holder: Streamlined inventory management for professionals on the move.
• Lifetime Warranty: Our legendary guarantee of excellence

CONFIGURATIONS



1726
Standard



1726NF
No Foam



1726WF
With Foam

DIMENSIONS

Interior (L×W×D)	38.90 x 12.98" x 12.93 (98.8 x 33 x 32.8 cm)
Exterior (L×W×D)	42.32 x 15.99" x 13.87 (107.5 x 40.6 x 35.2 cm)
Int Volume	3.78 ft³ (0.107 m³)

Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	
Latch	ABS
O-Ring	EPDM
Foam	Polyurethane
Purge Body	ABS
Purge Vent	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

WEIGHT

Weight With Foam	22.30 lbs (10.12 kg)
Weight Empty	17.90 lbs (8.12 kg)

TEMPERATURE

Minimum Temperature	0°F (-17.8 °C)
Maximum Temperature	140°F (60 °C)

Document created on 11-13-26